

READ THE OWNER'S MANUAL AND EXTINGUISHER LABEL.

READ ALL WARNINGS AND CAUTIONS ON THIS LABEL. IMPROPER USE COULD RESULT IN SERIOUS BODILY INJURY OR PROPERTY DAMAGE.

### IN CASE OF FIRE

\*When the extinguishing agent comes in contact with the fire, the fire will flare and appear to grow larger. This condition is a normal temporary reaction before the agent suppresses the fire. Continue to discharge contents.

\*Discharge time: approximately 8 to 12 seconds.

### SAFETY PRECAUTIONS

#### WARNING:

- \*Keep away from children.
- \*Do not incinerate.
- \*Do not discharge at a person's face.
- \*Do not store at high temperatures (above 120° F) or at extremely cold temperatures (below -40° F).
- \*Avoid inhaling the dry chemical agent.

#### CAUTION:

- \*DO NOT TEST. Any use will cause pressure loss.
- \*Discard extinguisher if dropped, damaged, dented or corroded in any way.
- \*Avoid exposure to contents if wearing contact lenses; or have respiratory illnesses or skin allergies.
- \*Although the agent contained in this extinguisher is not toxic, it may cause skin irritation. In case of contact with agent, flush from affected area with clean, cool water.

# INSTRUCTIONS

1. PULL PIN.  
HOLD UNIT  
UPRIGHT.



2. STAND BACK 6 FEET,  
AIM AT BASE OF  
FIRE.



3. SQUEEZE LEVER AND SWEEP  
SIDE TO  
SIDE.



**B** LIQUIDS • GREASE



**C** ELECTRICAL EQUIP.



\*If irritation persists, contact a physician immediately. The chemical name of agent is listed below.

\*Disposable Fire Extinguisher. Do Not attempt to refill and pressurize (recharge). Discard immediately after any use. Completely discharge unit before discarding.

### MAINTENANCE INSTRUCTIONS:

CHECK THE PRESSURE INDICATOR AND INSPECT EXTINGUISHER MONTHLY or more frequently if exposed to weather or vandalism. Indicator pointer must be in green area. If indicator pointer is not in the green area, extinguisher will not work properly and MUST BE DISCARDED. Examine nozzle for obstructions. Check that ring pull pin is intact. Extinguisher to be installed, inspected, maintained and tested in accordance with the standard of the National Fire Protection Association titled "Portable Fire Extinguishers" NFPA No. 10. Meets D.O.T. requirements for aluminum cylinders. Tested to 300 psi.

CONTENTS OF BC DRY CHEMICAL POWDER:  
SODIUM BICARBONATE, MICA, BARIUM  
STEARATE, NUISANCE DUST, IRRITANT;  
HMIS 0-0-0.

WALTER KIDDE  
THE FIRE EXTINGUISHER CO.  
1394 SOUTH THIRD ST.  
MEBANE, NC 27302-9199  
(919) 563-5911

LABEL PN 340191

# BC

# KIDDE

DRY CHEMICAL

# BC